

NO LIMITS


PACKAGING IS OUR BUSINESS

Packaging Machine PACKMAT F28 C



Features

- Angular inline packaging machine
- Profile construction allows flexible design
- Uses flat film (PE,PP,composite)
- Controlled film unwind
- Automatic sealing temperature control
- Air cooling systems
- Mechanical and electrical safety systems
- Optimal accessibility for service and fault finding (Swing out of the longitudinal sealing)
- Siemens S7-300 steering gear
- Ethernet port for data communication
- Clear operating station with coloured touchpanel
- Optimal operator-leading through enter-key masks and online-help
- Fault indication by clear text and indicator lamps
- Structured access-rights for machine-parameters through password-levels
- Data base
- Synchronisation for additional machines prepared



Technical Data

Cycling Speed:	up to max. 40 bags / min.
Bag width:	up to 280 mm
Bag length:	infinitely variable (mm)
Passage clearance:	90 mm
Film thickness:	approx. 40 bis 150 my
Electrical supply:	230 VAC / 50 Hz
Power Requirements:	max. 12 A
Compressed Air:	min. 5 bar
Dimensions:	approx. 1500x1300x1700 mm (LxBxH)
Weight:	approx. 200 kg

Options

- Thermotransfer-direct printer
- Labeller
- Linked bag chains
- Easy bag opening system
- Protection slider for sealing station
- Bagopener support
- Slider or flap in the filling tube
- Longitudinal- and transverse perforation
- Air hole punch
- Euro hole punch
- Hand feed table
- Other options on request

ABG-PACKMAT AG
Oldisstrasse 55
CH- 7023 Haldenstein
Phone +41 (0)81 354 10 00
Fax +41 (0)81 354 10 01
info@abg-packmat.ch
www.abg-packmat.ch

ABG-PACKMAT GmbH
Gewerbestrasse 4
D- 78667 Villingendorf
Phone +49 (0)741 928 10
Fax +49 (0)741 928 130
info@abg-packmat.de
www.abg-packmat.de

Technische Änderungen vorbehalten © 2010 ABG-PACKMAT AG

ABG PACKMAT
Verpackungsmaschinen und Zuführsysteme